



## STP MADELIN TAPE

**STP Madeline** is decorative self-adhesive anti-squeak material, used for automobile cabs, interiors, and boots lining.

### Composition

The material is a textile product (fabric, tapestry, unwoven or carpet fabric, etc.), with an adhesive mounting layer, protected with anti-adhesive film

### Linear dimensions

The material produced in coils

Package contains: 60 coils

Tape size: 15\*2000mm

### Advantages

Eliminates squeaks and bounces

Long-lived, reliable material

Easy to apply

### **Area of application**

Automobiles cabs, Interiors, Trunk (between plastic and metal details)

<b>Coefficient nomination</b>	<b>Specification</b>	<b>Testing method</b>
Durability of connection between the material and the metal surface during flaking-off, N/m, at least	3	TD 8729-010-48214265-2002
Durability of the adhesive covering connection with the sticky polymeric layer, N/cm	0,01-0,10	GOST 17317
Flammability, rate of combustion, mm/min, not more than	Non-flammable 100	GOST 25076
Adhesive layer resistance to temperature of 60°C during 24 h	The material must not peel off the mounting layer	TD 8729-010-48214265-2002

### **Storage instructions**

The coiled material packages must be stored horizontally in piles not higher than 2m on trays or shelves with plane surface in roofed warehouses not closer than 1m to heating appliances, under the conditions eliminating moisture penetration and exposure to sunlight.

### **Exploitation and installation requirements**

To install the material, the anti-adhesive film must be taken off. The material edge is to be put on the mounting surface and pressed step-by-step, without stretching, to the mounting surface, avoiding air blisters formation. The material must be installed on dry clean surfaces.

The material's operating temperature range is from -40°C to +60°C.

True extract  
 Quality Control Department Specialist  
 LLC "Standartplast"