



STP BITOPLAST TAPE

STP Bitoplast tape is self-adhesive, anti-squeak and sealing material, used for automobile cabs, interiors, and boots lining of different vehicles.

Composition

The material is elastic polyurethane foam, modified by bitumen composition with an adhesive layer protected with anti-adhesive film.

Linear dimensions

The material produced in coils

Package contains: 40 coils

Tape size: 15*2000mm

Advantages

Eliminates squeaks in the cabin

Thermal insulation properties

Long-lived, undecayable

Odorless

Keep properties at low temperature range

Area of application

Plastic door trim panels, plastic interior panels, wiring and lock rod, air duct

| Coefficient nomination | Specification | Testing method |
|---|-----------------------|---------------------------|
| Thickness, mm | 5 | TD 2254-019-48214265-2002 |
| Weight of 1m ² , mass kg, not less | 0,04kg/m ² | TD 2254-019-48214265-2002 |
| Durability of connection between the material and the metal surface during flaking-off, N/m, at least | 2 | TD 2254-019-48214265-2002 |
| Durability of the adhesive covering connection with the sticky polymeric layer, N/cm | 0,01-0,20 | GOST 17317 |
| Flammability, rate of combustion, mm/min, not more than | Non-flammable 100 | GOST 25076 |

Storage instructions

The materials must be stored at temperature not higher than 40°C, horizontally, on a plane surface, not closer than 1m from heating appliances, under the conditions eliminating moisture and oil penetration and exposure to sunlight, in piles not higher than 1,5 m.

Exploitation and installation requirements

To install the material, the anti-adhesive film must be taken off. The material edge is to be put on the mounting surface and pressed step-by-step, without stretching, to the mounting surface, avoiding air blisters formation. The material must be installed on dry clean surfaces.

True extract
 Quality Control Department Specialist
 LLC "Standartplast"